

ПРОГРЕСИВНИ И МОДУЛИРАЩИ ГАЗОВИ ГОРЕЛКИ F.B.R.



Модел	Мин. налягане пред рампата (mbar)	Мощност (kW)	Ел. захр.	Дълж. на главата (mm)
	Метан LPG	мин макс		
GAS X2/M CE TC+rampa GAS CE D3/4"-S	18 24	40,6 93	1F	85
GAS X2/M CE TL+rampa GAS CE D3/4"-S	18 24	40,6 93	1F	145
GAS X3/M CE TC+rampa GAS CE D1"-S	14 31	70 174	1F	130
GAS X3/M CE TL+rampa GAS CE D1"-S	14 31	70 174	1F	250
GAS X4/M CE TC +rampa GAS CE D1"-S	14 21	116 232	1F	160
GAS X4/M CE TL +rampa GAS CE D1"-S	14 21	116 232	1F	280
GAS X5/M CE TC+rampa GAS CE-CTQ D1"-S	27 33	151 349	1F	250
GAS X5/M CE TL+rampa GAS CE-CTQ D1"-S	27 33	151 349	1F	335
GAS XP 60/M CE TC+rampa GAS CE D11/2"-FS40	15 21	232 522	3F	250
GAS XP 60/M CE TL+rampa GAS CE D11/2"-FS40	15 21	232 522	3F	335
GAS P 70/M CE TC+rampa GAS/M CE D2"-FS50	17 25	406 754	3F	250
GAS P 70/M CE TL +rampa GAS/M CE D2"-FS50	17 25	406 754	3F	385
GAS P 100/M CE TC+rampa GAS/M CE D2"-FS50	33 31	580 1160	3F	250
GAS P 100/M CE TL+rampa GAS/M CE D2"-FS50	33 31	580 1160	3F	385
GAS P 150/M CE-03 TC+rampa GAS/M CE-CT D2"-FS50	57 49	814 1508	3F	280
GAS P 150/M CE-03 TL+rampa GAS/M CE-CT D2"-FS50	57 49	814 1508	3F	400
GAS P 150/M CE TC+rampa GAS/M CE-CT D2"-FS50	63 43	814 1744	3F	280

GAS P 150/M CE TL+rampa GAS/M CE-CT D2"-FS50	63 43	814 1744	3F	400
GAS P 190/M CE TL+rampa GAS/M CE-CT D2"-FS50	100 42	1044 2209	3F	500
GAS P 250/M CE TL+rampa GAS/M CE-CT D2"-FS50	184 80	1160 2900	3F	500
GAS P 350/M CE TL+rampa GAS/M CE-CT D2"-FS50	284 111	1392 4060	3F	520
GAS P 450/M CE TL+rampa GAS/M CE-CT D2"-FS50	450 176	1856 5220	3F	520
GAS P 550/M CE TL+rampa GAS/M CE-CT D2"-FS50	674 265	2320 6380	3F	520
GAS P 650/M CE TL+rampa GAS/M CE-CT DN65-FS65	400 200	3488 7558	3F	490